

Flip-Flap Doors Type P

Single- or double-leaf

Swing door hinge
V2A with
90° locking



Surface finish
Chrome-nickel steel
V2A circular matt finish

W. Ermeling & Söhne GmbH & Co. KG
Robert-Perthel-Straße 8 | 50739 Köln
Phone +49 (0)221 917 44 50
info@ermeling-soehne.de
www.ermeling-soehne.de



Ermeling & Söhne
Der Isoliertüren-Spezialist

Flip-Flap Doors

Type P

Typ P-1/P-2

Single- or double-leaf, full metal door leaf, pressure-injected PUR-high-resistance foam, CFC-free, leaf thickness 40 mm (K-value = 0.67 W/m² K), leaf edges protected by special elastic plastic profile, affixed with galvanized, double-side flip-flap door hinges, ready to be installed, visible sides metal panelled.

The stainless steel version with standard flip-flap door hinges in stainless steel.

Typ PP-1/PP-2

Single- or double-leaf full-plastic version in different colours, door-leaf of 15 mm polyethylene, integrated window, lock for both sides, with adjustable locking pressure.

Typ KP1/KP2

Single- or double-leaf transparent flip-flap doors, frame and gullows profile in galvanized or stainless steel (V2a).

„Trans“ version

Door leaf consisting of transparent PVC, 7mm thick.

„Leg“ version

Door leaf consisting of transparent PVC with break-resistant netting insert, 7mm thick.



Flip-Flap Doors

Type P

Installation sketch

