

# Freezer compartment extraction hatches

## Type MGL-1 / GDL-1

Insulating extraction hatches/ceiling hatches for special use in cold storage or storage rooms (plus range)



*Hatch lock black  
chrome-plated*

*Hatch hinges  
high gloss  
chrome-plated*

# Freezer compartment extraction hatches

## Type MGL-1 / GDL-1

### Door Leaves

Pressure-injected PUR-High-resistance foam, CFC-free, flame retardant according to DIN ISO 3285, all-round profiled joint, TPE grey, in grease resistant quality which can easily be exchanged.

### Door Frame

High-quality Nordic pine with respective metal panelling, ready to be installed with galvanized wall cramps. Full plastic frame (Stükanit) with metal panelling upon request.

### Handles

Highly-polished chromium-plated lock. Lockable with mini-cylinder and chromium-plated screw-on hinges upon request.

### Chill Room Hatch MKL-1

Leaf-thickness 80mm, K-value = 0.353 W/m<sup>2</sup>K).

### Freezer Room Hatch MGL-1

Leaf-thickness 130mm, K-value = 0.223 W/m<sup>2</sup>K), 220 Volt heating integrated in door frame (with VDE certificate) with bimetallic control.

**Hatch walls with any number of hatches or doors can be produced exactly to size.**



### Design

- ✓ In plastic-coated, galvanized sheet steel (Pladur), color: RAL 9002 or RAL 9010, fittings: black EPS-coated
- ✓ In aluminium sheet AlMg-3, circular matt design, or foil-coated galvanized sheet steel, color RAL 9001, fittings: black EPS-coated
- ✓ In chrome-nickel steel V2A, Mat. No. 4301, fittings: black EPS-coated
- ✓ Circular matt design or longitudinal cut (180 grain), fittings: black EPS-coated

# Freezer compartment extraction hatches Type MGL-1 / GDL-1

## Installation sketch

