

Sanitation room door

Type MH1 /MH2

Single-leaf (MH-1) or double-leaf (MH-2) insulated door for special use in operational, computer, and social rooms (wet area)



W. Ermeling & Söhne GmbH & Co. KG
Robert-Perthel-Straße 8 | 50739 Köln
Phone +49 (0)221 917 44 50
info@ermeling-soehne.de
www.ermeling-soehne.de

 **Ermeling & Söhne**
Der Isoliertüren-Spezialist

Sanitation room door

Type MH1 / MH2

Door Leaves

All-metal door leaf in special styling: with thermal bridge interrupter out of a plastic profile for stabilisation of the door leaf hinge plates. With rigid PUR foam, CFC-free, flame retardant according to DIN ISO 3285, insulated under high pressure, total door leaf thickness 40 mm (thermal transfer = 0.67 W/m²K) with inlaid foam insulated reinforced steel for the mounted fastener.

Door Frame

As all-metal border in a styling to be chosen by purchaser, welded. Replaceable with integrated sealing profile in grease-resistant quality.

Handles

„Behördenschloss“ (mortice lock adequate for high standards) class III with stainless steel cover. Profile barrel and circular-latchkey as rosette fitting (plastic black alternative chrome-nicle-steel). In three parts, nickel-plated strips.



Design

- ✔ Plastic-laminated, galvanized sheet steel (Pladur), color: white (RAL 9002 or RAL 9010)
- ✔ Aluminium sheet AlMg-3, circular brush design or foil-coated galvanized sheet steel, colour (RAL 9001).
- ✔ Chrome nickel steel V2a, Material No. 4301, circular brush or vertical brush design (grain size 180).

Sanitation room door

Type MH1 / MH2

Installation sketch

